



Glance tron GT15plus

LCD monitor with integrated touch screen

- High-end 38.1 cm (15") LCD monitor for demanding applications
- Integrated touch screen with 5-wire resistive touch technology
- Elegant design and particularly robust construction
- Dual interface: RS232 and USB for optimal integration
- Maximum resolution: 1024 x 768 pixels

Specifications

Display	Screen diagonal / type	38.1 cm (15") / LCD TFT active matrix
	Aspect ratio	4:3
	Resolution (max.)	1024 x 768 Pixel
	Active area (HxW)	304 x 228 mm
	Response time	Tr: 2 ms / Tf: 6 ms
	Colours	16.2 million
	Contrast	500:1
	Brightness	200 cd/m ²
	Viewing angle (H/V)	140° / 125°
	Video Input	VGA (analogue)
	Touch technology	Resistive (5-wire)
Touch interface	Dual interface (RS232/USB)	
General	Colour	Dark grey
	Dimensions (WxHxD)	364 x 320.4 x 205.4 mm (incl. stand) 364 x 295 x 61.5 mm (without stand)
	Weight	5,0 kg / 7,9 kg
	Power supply	Integrated power supply (AC input 100 ~ 240 V / DC 12 V)
	Power consumption	Operating: 25 W / Sleep: 4 W / Standby: 2 W
	Mounting options	Stand / VESA (75 x 75 mm)
	Control buttons	Power on/off, Menu, Select, Up, Down
	Audio	1 W speaker / 2-channel
	Certifications	TUV, CE, UL, CUL, FCC, RoHS, IPX1
	Drivers	Windows 7, VISTA, XP, 2000, ME, 98, NT4.0, CE, XP Embedded; Linux; Apple MacOS
	Options	n/a
Delivery contents	Monitor, stand, connection cables (USB, RS232, VGA, audio), power cord (EU), cable cover, driver CD, QSG	
Environment	Operating temperature	0 to +40°C
	Storage temperature	-20 to +60 °C
	Operating humidity	20 to 80 % (non-condensing)
	Storage humidity	10 to 90 % (non-condensing)



Your partner



Glance tron GT17plus

High-performance touch screen with an elegant design

- High-performance touch screen with a large 43.2 cm (17") screen diagonal
- Integrated touch screen with 5-wire resistive touch technology
- Elegant design and particularly robust construction
- Dual touch screen interface: RS232/USB
- Maximum resolution: 1280 x 1024 pixels

Specifications

Display	Screen diagonal / type	43.2 cm (17") / LCD TFT active matrix
	Aspect ratio	5:4
	Resolution (max.)	1280 x 1024 Pixel
	Active area (HxW)	338 x 270 mm
	Response time	Tr: 2 ms / Tf: 6 ms
	Colours	16.7 million
	Contrast	800:1
	Brightness	240 cd/m ²
	Viewing angle (H/V)	160° / 160°
	Video input	VGA (analogue)
	Touch technology	Resistive (5-wire)
Touch interface	Dual interface (RS232/USB)	
General	Colour	Dark grey
	Dimensions (WxHxD)	371 x 400 x 225 mm (incl. stand) 371 x 338 x 68.6 mm (without stand)
	Weight	7,3 kg / 9,3 kg
	Power supply	Integrated power supply (AC input 90 ~ 264 V / DC 12 V)
	Power consumption	Operating: 36 W / Sleep: 4 W / Standby: 2 W
	Mounting options	Stand / VESA (100 x 100 mm)
	Control buttons	Power on/off, Menu, Select, Up, Down
	Audio	1 W speaker / 2-channel
	Certifications	TUV, CE, UL, CUL, FCC, RoHS
	Drivers	Windows 7, VISTA, XP, 2000, ME, 98, NT4.0, CE, XP Embedded; Linux; Apple MacOS
	Options	n/a
Delivery contents	Monitor, stand, connection cables (USB, RS232, VGA, audio), power cord (EU, UK), cable cover, driver CD, QSG	
Environment	Operating temperature	0 to +40 °C
	Storage temperature	-20 to +60 °C
	Operating humidity	20 to 80 % (non-condensing)
	Storage humidity	10 to 90 % (non-condensing)



Your partner



Glancetron GT19plus

Professional high-end monitor with an elegant design

- Flagship of the GTplus series of professional high-end monitors with its 48.3 cm (19") touch screen
- Integrated touch screen with resistive touch technology
- Elegant design and particularly robust construction
- Dual touch screen interface: RS232/USB
- Maximum resolution: 1280 x 1024 pixels

Specifications

Display	Screen diagonal / type	48.3 cm (19") / LCD TFT active matrix
	Aspect ratio	5:4
	Resolution (max.)	1280 x 1024 Pixel
	Active area (HxW)	376 x 301 mm
	Response time	Tr: 3,6 ms / Tf: 1,4 ms
	Colours	16.7 million
	Contrast	800:1
	Brightness	200 cd/m ²
	Viewing angle (H/V)	160° / 160°
	Video input	VGA (analogue) / DVI-D (digital)
	Touch technology	Resistive (5-wire)
Touch interface	Dual interface (RS232/USB)	
General	Colour	Dark grey
	Dimensions (WxHxD)	438 x 407.8 x 267.4 mm (incl. stand) 438 x 370 x 67.9 mm (without stand)
	Weight	10 kg / 12kg
	Power supply	Integrated power supply (AC input 90 ~ 264 V / DC 12 V)
	Power consumption	Operating: 25 W / Sleep: 3 W / Standby: 1 W
	Mounting options	Stand / VESA (100 x 100 mm)
	Control buttons	Power on/off, Menu, Select, Up, Down
	Audio	1 W speaker / 2-channel
	Certifications	TUV, CE, UL, CUL, FCC, RoHS
	Drivers	Windows 7, VISTA, XP, 2000, ME, 98, NT4.0, CE, XP Embedded; Linux; Apple MacOS
	Options	n/a
Delivery contents	Monitor, stand, connection cables (USB, RS232, VGA, DVI, audio), power cord (EU, UK), cable cover, driver CD, QSG	
Environment	Operating temperature	0 to +40 °C
	Storage temperature	-20 to +60 °C
	Operating humidity	20 to 80 % (non-condensing)
	Storage humidity	10 to 90 % (non-condensing)



Your partner